

Our new Spendor D-Line loudspeakers combine cuttingedge research and technical innovation with real-world design. They bring captivating sound quality to the music you love and fit easily and unobtrusively into any setting.

Compatible with all good amplifiers, the floorstanding D7 and D9 deliver exceptional resolution and low-frequency power, communicating a vibrant realism to music of all genres. With their slim enclosures and smart modern finishes, they're easy to place in dedicated listening rooms or everyday living spaces. The Spendor D1 is the smallest in the line, and a worthy successor to our award-winning SA1. It's designed to deliver a naturally balanced sound with amazing clarity and definition, even when positioned close to a wall or on a bookshelf, making it effortlessly at home anywhere.

DI

All D-Line loudspeakers draw on our research into cabinet damping, advanced polymers, amplifier-loudspeaker interface, low-frequency airflow and sound behaviour. An inspiring and satisfying choice for audiophiles and discerning music-lovers.

HIGHLIGHTS

- Spendor LPZ high frequency driver
- Fifth Generation Twin-Venturi Linear-Flow port (D7 & D9)
- New Spendor EP77 Polymer cones
- New Kevlar composite cone low frequency bass drivers
- Spendor Dynamic Damping cabinet technology
- Five elegant natural veneer finishes with premium options
- Multi-Award winning
- Calibrated and matched to broadcast reference standard
- British design and manufacture

| MODEL | DESCRIPTION | DRIVE UNITS | $H\times W\times D$ | WEIGHT |
|-------|-------------------------|---------------------------------|---------------------|--------|
| DI | 2-way shelf/stand mount | LF 150mm, HF 22mm | 305 x 165 x 185mm | 5.7kg |
| D7 | 2.5-way floorstanding | 2 x LF 180mm, HF 22mm | 950 x 192 x 333mm | 21kg |
| D9 | 3-way floorstanding | I × MF & 2 × LF I 80mm, HF 22mm | 1125 x 210 x 398mm | 35kg |

| MODEL | RESPONSE | IMPEDANCE | AMPLIFIER | SENSITIVITY | CROSSOVER |
|-------|--------------|-----------|-------------|-------------|---------------|
| DI | 55Hz - 25kHz | 8 Ohms | 25-100watts | 85dB | 4.8kHz |
| D7 | 29Hz - 25kHz | 8 Ohms | 25-200watts | 90dB | 900Hz, 3.2kHz |
| D9 | 27Hz - 25kHz | 8 Ohms | 25-250watts | 90dB | 500Hz, 4.2kHz |



D7



D9



Spendor Audio Systems Ltd, G5 Ropemaker Park, South Road, Hailsham, East Sussex BN27 3GY UK +44 (0)1323 843474 info@spendoraudio.com **spendoraudio.com**

TECHNICAL SPECIFICATION