

FURUTECH

PURE TRANSMISSION



e-TP86E(G) AC Power Distributor

Slimline Power Series



Type: 2-Pole + Earth • Rating: 10A 250V AC

Furutech's Award-Winning Pure Transmission Build Quality

Total Attention to Detail and Build Quality

Many A/V enthusiasts go to great lengths to carefully set up major system components, but pay little attention to the source, the AC power. Furutech knows that each and every part of the chain is as important as the next, so maximum attention is lavished by Furutech on *all* aspects of AC power transfer.

The specially crafted high-grade aluminum chassis effectively shields against another common problem, RFI (Radio Frequency Interference). Internal wiring is Furutech μ -14, 2.0 sq. mm (14 AWG) guaranteeing low electrical resistance. Furutech FI-E30(G) 16A high performance gold-plated schuko sockets are wired to a high performance FI-06(G) IEC. The schuko sockets feature non-magnetic gold-plated copper alloy conductors for stable, long lasting, optimized power transfer.

The e-TP86E(G) will allow the delicacy, refinement and nuance of a performance through, along with micro- and macro-dynamics that will leave you breathlessly engaged. Displays of all types will exhibit greater, sharper resolution with less ghosting, color shift, "snow", or vertical and horizontal lines.

Features:

- Beautifully-crafted high-grade aluminum chassis
 - Effectively shields against RFI (Radio Frequency Interference)
- Original T-model reinforced aluminum chassis supporter for strength and stability
- Internal wiring: Furutech μ -14 conductor at 2.0 sq. mm (14 AWG)
 - Guarantees low electrical resistance
- Pure Transmission FI-E30(G) 16A high performance gold-plated SCHUKO Socket
 - Wired to high performance FI-06(G) IEC inlet
 - High performance circuit breaker
 - Special damping material set under schuko socket
 - Non-magnetic gold-plated copper alloy, conductors for stable, long lasting, optimized power transfer

ALL metallic parts used in Furutech products go through the Alpha Process treatment to keep all connectors, conductors, and metal parts in a perfect stress-free, stable and highly conductive state.

Electrical Specifications:

<div>TYPE</div> <div>SPECIFICATION</div>	e-TP86E(G)	<div>TYPE</div> <div>SPECIFICATION</div>	e-TP86E(G)
RATING	250V AC 50/60Hz	MOVEMENT TEMP.	-10°C~40°C
CURRENT	10 A	PRESERVATIVE TEMP.	-20°C~50°C
WATTS.	Total 2500W max.	OVER LOAD Protection	Circuit breaker (Reset type)
OUTLETS	8 Outlets	BODY MATERIAL	AL. ALLOY
OUTWARD SIZE	516 L x 77.2 W x 48.8 H mm approx.	WEIGHT (Net.)	1.14 Kg approx.

Make A More Powerful Connection with Furutech!
FURUTECH CO., LTD • service@furutech.com • www.furutech.com

Product name	Product Introduction	JAN CODE
e-TP86E(G)	High Performance AC Power Distributor	
e-TP86E(R)	High Performance AC Power Distributor	By Request